



Steam Generators



LAB-101-154



LAB-102-423



LAB-102-423/SG

LAB-101-154

Laboratory mini steam generator

Table top version with small footprint only 26 x 30 x 37 centimetres, small weight (empty) 7.4 kg

Equipped with:

- Analog steam pressure indicator
 - Visual water level indicator
 - Solenoid steam flow valve with adjuster knob
 - Automatic safety water tap
- Boiler: INOX 3,4 lt
 - Autonomy: 3.0 hours
 - Steam pressure: 2,8-3 bar
 - Heating power: 1,45 KW
 - Power supply:
230 V - 50/60 Hz
115 V - 60 Hz

LAB-102-423

Industrial Steam Generator

Floor version with motion wheels and footprint 50 x 52 x 90 centimetres, weight (empty) 46 kg

Equipped with:

- Analog steam pressure indicator
 - Rear feeding tank capacity 20 liters with visual water level indicator
 - Solenoid steam flow valve with adjuster knob
 - Automatic overpressure valve
 - Manual drain valve
- Boiler: INOX 8,5 lt
 - Steam pressure: 4.5 bar
 - Steam production: 5.2 kg/hour
 - Heating power: 4 KW
 - Power supply:
230 V - 50/60 Hz - 1 ph

LAB-102-423/SG

Heavy Industrial Steam Generator

Floor version with motion wheels and footprint 70 x 58 x 70 centimetres, weight (empty) 65 kg

Equipped with:

- Analog steam pressure indicator
 - Integrated built-in water pump 0.7 HP water line connection needed
 - Manual steam flow valve
 - Automatic overpressure valve
 - Manual drain valve
- Boiler: INOX 17 lt
 - Steam pressure: 5 bar
 - Steam production: 19.5 Kg/hour
 - Heating power: 18 KW
 - Power supply:
400 V - 50/60 Hz - 3 ph